

This infrared thermometer series is robust and easy to use. Users can measure the surface temperature without contacting the object. UT306 series can be used in various fields such as food industry, machine maintenance, metal working, cold storage, and other industrial fields.



UT306S



UT306C

Specifications	UT306S	UT306C
Certificates		CE, UKCA
Temperature range	-50°C~500°C	-50°C~500°C
Laser type	single	circle
Accuracy	±2°C or ±2%	±2°C or ±2%
Resolution	0.1°C	0.1°C
D:S ratio	12:1	12:1
Response time	250ms	250ms
Emissivity	0.10~1.00 Adjustable	0.10~1.00 Adjustable
Laser class	Class 2	Class 2
Laser power	<1mW	<1mW
Laser wavelength	630nm~670nm	630nm~670nm
Spectral response	8μm~14μm	8μm~14μm

Features		
Display type	TN-LCD	EBTN-LCD
Unit selection	°C/°F	
Laser on/off	√	
Data hold	√	
Auto power off	√	
Low battery Indication	√	
MAX/MIN/AVG/DIF mode	√	
High temperature alarm (audible)	√	
Drop test	1m	

Characteristics	
Power	1.5V AAA x 2
Product net weight	161.5g
Product size	146 x 78 x 45mm
Standard accessories	Batteries
Standard individual packing	Card, blister, manual
Standard quantity per carton	20pcs
Standard carton measurement	515 x 375 x 175mm